



Kodak EasyShare C875

Zoom Digital Camera

Get closer to what's important

Want to know a secret about this impressive camera? It's also incredibly simple to use. So get close and print big with 5X optical zoom and 8.0 MP. And shoot with confidence using features like smart scene mode and Kodak Perfect Touch technology. The Kodak EasyShare C875 zoom digital camera – some secrets are meant to be shared.

Unbelievable picture quality

- Create exceptional quality prints up to 76 x 102 cm (30" x 40") with this 8.0 MP camera
- Get closer to your subjects with its professional quality 5X, all glass Schneider-Kreuznach optical zoom lens
- Get remarkable results thanks to on-camera features such as Kodak Perfect Touch technology, cropping, digital red-eye removal, blurry picture alert, and undo-delete
- Combine up to three shots together into one large picture with panorama stitch mode
- Reduce blur in Sport and Children modes with anti-blur technology
- Get rich, vibrant color under a variety of lighting conditions with the exclusive Kodak color science chip

Incredible ease of use

- Capture stunning shots with ease – smart scene automatically selects the best scene mode
- Convenience features such as on-camera help and auto picture rotation make picture taking simple



- Get creative with advanced settings and custom controls, including program, aperture and shutter priority, and full manual mode (PASM)
- Get the right shot – manually select from 21 programmed scene and 5 color modes
- Don't miss a shot if your memory card becomes full – switch to in-camera memory quickly, thanks to the internal memory plus feature
- Works with optional Kodak EasyShare G600 printer dock, Kodak EasyShare photo printer 500, Kodak EasyShare printer dock plus series 3, and Kodak EasyShare camera dock series 3

The simple way to share

- View your pictures with clarity on its large 6.4 cm (2.5") indoor/outdoor color display featuring a wide viewing angle
- Capture life in motion with TV quality (VGA) video at 30 fps
- Create prints from video (4, 9, or 16 up), plus view and share single frames
 - Features audio capture, playback, and on-camera video editing
 - Capture more video using less memory with MPEG-4 compression
- Print, e-mail, and organize your pictures with just one touch of our exclusive on-camera Share button
- Use Favorites to keep your special pictures close

Kodak EasyShare C875

Zoom Digital Camera

Standard features

Sensor type	1/1.8" CCD
CCD total pixels	8.3 MP (3350x2483)
Effective pixels	8.0 MP (3273x2457)
Lens	5X optical, 37-185 mm (35 mm equiv.) f/2.8-4.4, 12 step aperture
Lens barrier	built-in lens barrier
Zoom	5X optical; 5X continuous digital with LCD preview, 0.2X increments
Shutter speed	8-1/1600 second
LCD	6.4 cm (2.5") wide-angle viewing
Storage	32 MB* internal memory, SD/MMC card expansion slot

Auto focus

Type	TTL-AF, manual
Focus range	normal wide: 0.6 m (2.0')-infinity; normal tele: 1.0 m (3.3')-infinity; macro, wide: 0.1-0.7 m (4"-2.3"); macro, tele: 0.7-1.0 m (2.3'-3.3')

Modes	single, continuous, selectable
Zones	Multi-zone and center zone
AF assist light	low light AF with AF assist LED

Exposure control

ISO sensitivity	auto: ISO 64-200; manual: ISO 64, 100, 200, 400, 800 (selectable in PASM)
Metering	TTL-AE, multi-pattern AE, center weighted AE, center spot AE
Compensation	±2.0 EV with 0.3 EV steps with flash compensation
Bracketing	3 images selectable ±0.3, 0.7, 1.0 steps
Histogram	yes
White balance	auto, daylight, tungsten, fluorescent, open shade, custom
Anti-blur	yes, in sport and children mode

Flash

Range	0.6-4.1 m (2.0-13.5') at wide, ISO 200; 0.6-2.6 m (2.0-8.5') at tele, ISO 200
Modes	auto, fill off, red-eye reduction

Shooting Specifications

Drive modes	self-timer, 2 and 10 seconds, and 2-shot; first burst: 2 fps, saves 5 images; last burst: 2 fps, saves last 4 images
Shooting modes	smart scene, PASM, custom, video
Scene modes	portrait, night portrait, landscape, night landscape, close-up, sports, snow, beach, text/document, backlight, manner/museum, fireworks, party, children, flower, self portrait, sunset, panorama left-right, panorama right-left, candlelight, panning shot
Click to capture	<0.6 sec. wide (preview on)
Shot to shot	<1.5 sec. interval until buffer full (6 shots), <5.6 sec. after buffer full

Still capture

Still format	JPEG/EXIF v 2.21
Picture size	8.0 MP - best (3264x2448), prints up to 30"x40";
(recorded pixels)	7.1 MP - best 3:2 (3264x2176), optimized ratio for 4"x6" prints;
	5.0 MP - better (2560x1920), prints up to 20"x30";
	3.1 MP - good (2048x1536), prints up to 8"x10";
	1.1 MP - e-mail (1200x900), small prints

Color modes	high color, natural color (default), low color, sepia, black and white
Sharpness	sharp, standard, soft
Review options	select all, view by, album, slide show, multi-up, copy, protect, image storage, set up menu

Editing	Kodak Perfect Touch technology, crop
---------	--------------------------------------

Video capture

Format	QuickTime MOV (MPEG-4) with audio recording during capture
Quality	VGA (640x480) at 30 fps, QVGA (320x240) at 30 fps
Length	<80 min.
Review options	select all, view by, album, slide show, multi-up, copy, protect, image storage, set up menu
Editing	make picture, edit video

Customization

Custom settings	picture size, set album, image storage, camera sounds, sound volume, LCD brightness, auto power off, date and time, video out, orientation sensor, red eye preflash, date stamp, video date display, blur warning, language
-----------------	---

Dedicated buttons	menu, review, Share, dedicated delete, 5-way switch for navigation, shutter, mode dial (off, on, PASM, C, scene, movie, Favorites), flash settings, burst/timer, LCD information button
-------------------	---

Favorites

Favorites	slide show, multi-up, remove Favorites, set-up menu
-----------	---

Physical specifications

I/O interface	NTSC or PAL, selectable via dock connector, exclusive Kodak camera dock/printer dock interface, digital (USB 2.0) connector
Power	optional Kodak EasyShare docks with 1 Kodak Ni-MH rechargeable digital camera battery KAA2HR; 2 Kodak oxy-alkaline digital camera batteries AA; 2 Kodak Ni-MH rechargeable digital camera batteries AA; 1 Kodak lithium digital camera battery CRV3; 2 lithium batteries AA; 3 volt DC input AC adapter
Tripod mount	1/4" standard
Dimensions	WxHxD: 90.5x63x36.6 mm (3.6"x2.5"x1.4")
Weight	without batteries: 177 g (6.2 oz.)

Compatibility

Dock compatibility	works with optional Kodak EasyShare G600 printer dock, Kodak EasyShare camera dock series 3
Direct print	Kodak EasyShare photo printer 500, ImageLink print system compatible, PictBridge enabled
Software	works with Kodak EasyShare software

Service and support

Warranty	one year
----------	----------

Minimum system requirements

Windows	Windows XP, SP4 or later, 600 MHz processor or greater; Internet Explorer 6.0 or higher
Macintosh	Macintosh OS X 10.3 or higher; Safari 1.1 or higher

Minimum hardware requirements

128 MB RAM; 200 MB hard drive disk space available; CD-ROM drive, available USB port; color monitor, 800x600 display resolution, 16-bit minimum

Package contents

Kodak EasyShare C875 zoom digital camera
Kodak oxy-alkaline digital camera batteries AA
USB/AV cables
Wrist strap
Kodak EasyShare software
Getting started guide
Custom camera insert for optional Kodak EasyShare camera and printer docks

Ordering information

Kodak EasyShare C875 zoom digital camera (U.S. and Canada)xxx xxxx

Recommended accessories

Kodak EasyShare G600 printer dockxxx xxxx
Kodak EasyShare photo printer 500xxx xxxx
Kodak color cartridge and photo paper kitxxx xxxx
Kodak EasyShare camera dock series 3xxx xxxx
Kodak EasyShare picture viewerxxx xxxx
Kodak SD memory cards 1 GBxxx xxxx
512 MBxxx xxxx
Kodak Ni-MH rechargeable batteryxxx xxxx
Kodak Ni-MH rapid battery charger kitxxx xxxx
Kodak 8-in-1 card readerxxx xxxx
Kodak small camera bagxxx xxxx
Kodak travel kitxxx xxxx
Kodak EasyShare starter kitxxx xxxx

*32 MB internal memory/28 MB available for picture storage (1 MB equals one million bytes).

For more information on the Kodak EasyShare C875 zoom digital camera, visit www.kodak.com/go/easysshare



©Eastman Kodak Company, 2006. Kodak, EasyShare, Perfect Touch, and ImageLink and the ImageLink print system logo are trademarks of Eastman Kodak Company. Schneider-Kreuznach is a trademark of Jos. Schneider Optische Werke GmbH used under license by Eastman Kodak Company. QuickTime and the QuickTime logo are trademarks or registered trademarks of Apple Computer, Inc., used under license therefrom. Product specifications subject to change without prior notice. Simulated screen images. IC-xxxx CAT No. xxx xxxx